



# TECH ANTIABRASIVE F-180



**Manguera de caucho SBR CONDUCTIVO según NORMA BS EN ISO 8031 con polímeros especiales, reforzada con una espiral de PVC rígido indeformable. Antiabrasiva y conductiva (formulación especial, sin hilo de cobre)**

Aspiración de materiales secos muy abrasivos, piedra, arena, cemento, carbón, tierra, virutas, polvo de hierro, aguas negras, maquinaria agrícola, purines, fibras textiles y pellet

Los valores de vacío y presión corresponden a temperaturas de trabajo de 23+2°C (ISO 291)

**CONDUCTIVE SBR rubber hose conforming to BS EN ISO 8031 with special polymers, reinforced with a rigid, non-deformable PVC spiral. Anti-abrasive and conductive (special formulation, without copper wire)**

Suction of highly abrasive dry materials, stone, sand, cement, coal, soil, shavings, iron dust, sewage, agricultural machinery, slurry, textile fibers and pellets

The detailed values of resistance to vacuum and pressure correspond to working temperatures between 23+2°C (ISO 291)

## ESPECIFICACIONES TÉCNICAS:

### TECHNICAL SPECIFICATIONS:

**Interior:** Superficie lisa en caucho

SBR CONDUCTIVO

**Inside:** Smooth CONDUCTIVE

SBR surface

**Exterior:** Corrugado

**Outside:** Corrugated

**Temperatura:** -40°C a +60°C

**Temperature:** -40°C to +60°C

**Colores disponibles**

**Available colours**

052



NUEVA  
GAMA  
CAUCHO

| Código<br>Code | Ø INT (mm)<br>Ø INS (mm) | Ø EXT (mm)<br>Ø EXT (mm) | Peso (gr/m)<br>Weight (gr/m) | Min. R. curvatura (mm)<br>Min. Bending R. (mm) | Presión de trabajo (bar)<br>Working pressure (bar) | Vacio (mH2O)<br>Vacuum (mH2O) | Longitud (m)<br>Length (m) |
|----------------|--------------------------|--------------------------|------------------------------|------------------------------------------------|----------------------------------------------------|-------------------------------|----------------------------|
| 052038         | 38                       | 47                       | 550                          | 51                                             | 2,4                                                | 10,02                         | 30                         |
| 052050         | 50,8                     | 62                       | 833                          | 63,74                                          | 2,4                                                | 10,02                         | 30                         |
| 052060         | 60                       | 74                       | 1.000                        | 60                                             | 2                                                  | 10,02                         | 30                         |
| 052063         | 63,5                     | 77                       | 1.204                        | 63,74                                          | 2                                                  | 10,02                         | 30                         |
| 052076         | 76,2                     | 90                       | 1.600                        | 76,5                                           | 2                                                  | 10,02                         | 30                         |
| 052090         | 88,9                     | 104,3                    | 2.000                        | 102                                            | 2                                                  | 10,02                         | 30                         |
| 052102         | 101,6                    | 117,6                    | 2.474                        | 114,75                                         | 2                                                  | 10,02                         | 30                         |
| 052127         | 126,8                    | 145,5                    | 3.600                        | 127,5                                          | 2                                                  | 9,68                          | 30                         |
| 052152         | 152,4                    | 171                      | 4.590                        | 234,6                                          | 2                                                  | 9,68                          | 30                         |
| 052200         | 203,2                    | 229,6                    | 8.410                        | 382,5                                          | 2                                                  | 9,33                          | 10                         |

Otros diámetros y colores, consultar.

Other diameters and colours, consult.